

# MF 1M

20 - 25 HP

THE MF 1M SERIES REPRESENTS THE NEXT GENERATION OF COMPACT TRACTORS, COMBINING MODERN DESIGN WITH ROBUST EFFICIENCY.

## RELIABLE PERFORMANCE IN A **COMPACT DESIGN**

Perfect for municipalities, equine, and leisure industries, as well as estate management and grounds care, these machines operate with smooth precision in confined spaces, low buildings and areas with restricted access.

They come with features that enhance convenience and ease of operation to save you time and give you the versatility you need to handle any task your day serves up.



MASSEY FERGUSON

BORN TO **FARM**

## SPECIFICATIONS

ENGINE	MF 1M.20		MF 1M.25	
Power (rpm)	hp (kW)	20 (14.3) @ 2,500 rpm	25 (18.2) @ 2,500 rpm	
Cylinders/capacity	No./cc	3/1,123	3/1,498	
Fuel tank capacity	litre	28		
TRANSMISSION TYPE				
		● Mechanical	● Hydrostatic	
POWER TAKE-OFF				
Engagement		Sliding gear	Independent	
Rear PTO speeds	rpm	540		
Mid PTO		—	●	
WHEELS AND TYRES				
Agricultural tyres	Front Rear	6.00-12 9.5-18		
Turf tyres	Front Rear	24x8.50-12 315x75D-15		
REAR AXLE				
Differential Lock		● RHS Pedal	● LHS Pedal	
Brakes, internal, wet disc		●		
3-point linkage, Cat 1		●		
Lift capacity	kg	650	900	
Hydraulic pump capacity	litre/min	20.9		
Spool valves		1	2	
ROPS, MID folding		●	—	
ROPS, REAR folding		—	●	
Cab		—	○	
WEIGHTS AND DIMENSIONS				
Weight	kg	870	1,060 (905 with ROPS)	
Overall length/height/width	mm	2,945/2,020/1,160	2,945/2,420/1,160	
Wheelbase	mm	1,560		
OTHER EQUIPMENT				
Front PTO		—	○ (cab version)	
Front linkage		—	○ (cab version)	
Opening bonnet, road lighting		●		
Rear view mirrors on both sides		●		
Hand grips and footstep		●		
Beacon light switch		●		

## MF 1M

THE MF 1M SERIES INCLUDES TWO MODELS: THE MF 1M.20 WITH 20 HP AND A 9F/9R MECHANICAL TRANSMISSION FOR PRECISE CONTROL, AND THE MF 1M.25 WITH 25 HP AND A HYDROSTATIC TRANSMISSION FOR SMOOTH OPERATION.

A ROPS is standard on both models, while the MF 1M.25 offers an optional cab. Both tractors provide operators with exceptional visibility and easy-to-reach controls, with an adjustable steering column ensuring a comfortable seating position.

- ▶ On the cab model, comfort and convenience are further enhanced by a wide range of standard equipment, including air conditioning a new hydraulic joystick, and LED worklights.
- ▶ With a dedicated 12.3 l/min pump for steering, all the flow from the main 20.9 l/min hydraulic pump is available through up to two spool valves for powering implements. Both models are extremely versatile, with lift capacity up to 900 kg.
- ▶ A new range of mid-mounted grass cutter decks offers additional options. For the MF 1M.25, customers can choose between a 54-inch mulching deck or a 60-inch side discharge model.
- ▶ The Mower Deck Override system makes fitting and removal easy with the tractor able to simply drive onto and over the deck.
- ▶ Choose the tyre tread and size that are right for your jobs and performance needs: ag, turf and industrial.
- ▶ A factory-fitted front linkage is an option for the MF 1M.25, enhancing versatility by allowing the use of front-mounted implements. Additionally, the aftersales-fitted front loader provides increased functionality for tasks such as lifting and transporting materials
- ▶ Ease of access and straightforward routine maintenance are made possible by the one-piece bonnet that will remain in a fully-opened position while checks and servicing are carried out.

- = Standard
- = Optional
- = Not applicable/available

For even greater productivity a range of optional equipment is available. For full details please contact your local Massey Ferguson Dealer.

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.



MASSEY FERGUSON® is a worldwide brand of AGCO.  
© AGCO Corporation. | A-A-18269 | English